

NVR1B04/1B08HC/E

4/8 Channel Cooper 1U H.265 Network Video Recorder



- · H.265+/H.264+ codec decoding
- Max 40Mbps/20Mpbs incoming/outgoing bandwidth
- Max 4/8 channel IP camera inputs
- Up to 6MP resolution preview&playback
- Up to 1ch@6MP/4ch@1080P 25fps decoding
- · HDMI/VGA simultaneous video output











System Overview

EZ-IP is perfect for small to medium size applications like home/ residential security, small retail shops, and other typical SMB applications. It offers a perfect alternative to migrate from analog to an IP system with its easy to use nature and cost effectiveness.

EZ-IP is fully in line with Dahua's quality. Stable and reliable components are utilized and Various tests such as anti-vibration, water resistance, and aging tests are performed to ensure Dahua quality standards.

Functions

Smart H.265+

Smart H.265+ is the optimized implementation of the H.265 codec that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality video without straining the network. Smart H.265+ technology reduces bit rate and storage requirements by up to 70% when compared to standard H.265 video compression.

Automatic Network Replenishment (ANR) Technology

Network Video Recorders with the ANR function automatically store video data on an IP camera SD card when the network is disconnected. After recovery of the network, the NVR automatically retrieves the video data stored on the camera.

DMSS

The DMSS app is available on the iOS App Store and Google Play. It makes surveillance easy and simple, allowing you to remotely access NVR devices, view live video, receive event push notifications, and search for recorded videos from an iPhone, iPad, or Android phone at anytime from virtually anywhere.




Technical Specification		Third-party Support		
System		Third nautu Cunnaut	Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco,	
Main Processor	Dual-core embedded processor	Third-party Support	Samsung, Sanyo, Sony, Videotec, and more	
Operating System	Embedded LINUX	Network		
Audio and Video		Interface	1 RJ-45 port (10/100Mbps)	
IP Camera Input	4/8 Channel	Network Function	HTTP/HTTPS, TCP/IP, IPv4/IPv6, RTSP, UDP, NTP, DHCP, DNS, IP Filter, IP Search(Support Dahua IP camera, DVR, NVS and etc.), P2P	
Two-way Talk	N/A	Optical Fiber Interface	N/A	
Display		Max. User Access	128 users	
Interface	1 HDMI, 1 VGA	Smart Phone	iPhone, iPad, Android	
Resolution	1920×1080, 1280×1024, 1280×720	Interoperability	ONVIF ,SDK, CGI Conformant	
Decoding Capacity	1ch@6MP 30fps, 4ch@1080P 25fps		OWNII , JUN, COI COMOTHAIL	
	4CH: 1/4	Storage	1 CATA III Dank was to ATD consolity for each LIDD	
Multi-screen Display	8CH: 1/4/8/9	Internal HDD	1 SATA III Port, up to 4TB capacity for each HDD	
OSD	Camera title, Time, Camera lock, Motion detection,	HDD Mode	Single	
	Recording	eSATA	N/A	
Recording		Auxiliary Interface	Auxiliary Interface	
Compression	H.265+/H.264+	USB	2 ports (2 Rear USB2.0)	
Resolution	6MP/5MP/4MP/3MP/1080P/ 720P/ D1&etc.	RS232	N/A	
Record Rate	40Mbps	RS485	N/A	
Bit Rate	16Kbps ∼ 20Mbps Per Channel	Electrical		
Record Mode	Manual, Schedule (Regular (Continuous), MD, Stop	Power Supply	Single, DC12V/1.5A	
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec,	Power Consumption	<2.57W (without HDD)	
Post-record: 10~300 sec Video Detection and Alarm		Environmental		
Trigger Events	Recording, PTZ, Tour, Video Push, Snapshot, and	Operating Conditions	-10°C ~ +45°C (+14°F ~ +113°F), 86 ~ 106kpa	
	Screen Tips Motion Detection, MD Zones: 396 (22 × 18),	Storage Conditions	-20°C ~ +70°C (-4°F ~ +158°F), 0 ~ 90% RH	
Video Detection	and Tampering	Construction		
Alarm input	N/A	Dimensions(W×D×H)	Cooper 1U, 197mm×196.6mm×41.5mm (7.76" x 7.74" x 1.63")	
Relay Output	N/A	Net Weight	1.15 kg (2.54 lb) (without HDD)	
Playback and Backup		Gross Weight	1.65kg(3.64 lb)(without HDD)	
Sync Playback	4CH: 1/4	Certifications		
	8CH: 1/4/9	CE	EN55032, EN55024, EN50130-4, EN60950-1	
Search Mode	Time /Date, MD and Exact Search (accurate to second)	FCC	Part 15 Subpart B, ANSI C63.4-2014	
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Backup Selection, Digital Zoom			
Backup Mode	USB Device/Network			

EZ-IP | NVR1B04/1B08HC/E

Ordering Information			
Туре	Part Number	Description	
4 Channel NVR	NVR1B04HC/E	4 Channel Cooper 1U H.265 Network Video Recorder	
8 Channel NVR	NVR1B08HC/E	8 Channel Cooper 1U H.265 Network Video Recorder	
Accessories	N/A	N/A	

Rear Panel



Dimensions (mm)

